

CERTIFICATE OF CONFORMITY

Issued to: FOXESS CO., LTD.
No.939, Jinhai Third Road, New Airport Industry Area, Longwan District, Wenzhou,
Zhejiang, China

For the product: Storage Inverter

Trade name:



Type/Model: H3-Pro-10.0, H3-Pro-12.0, H3-Pro-15.0, H3-Pro-20.0, H3-Pro-22.0, H3-Pro-24.9,
H3-Pro-25.0, H3-Pro-29.9, H3-Pro-30.0
AC3-Pro-10.0, AC3-Pro-12.0, AC3-Pro-15.0, AC3-Pro-20.0, AC3-Pro-22.0,
AC3-Pro-24.9, AC3-Pro-25.0, AC3-Pro-29.9, AC3-Pro-30.0
P3-Pro-10.0, P3-Pro-12.0, P3-Pro-15.0, P3-Pro-20.0, P3-Pro-22.0, P3-Pro-24.9,
P3-Pro-25.0, P3-Pro-29.9, P3-Pro-30.0
P3-Pro-10.0-AC, P3-Pro-12.0-AC, P3-Pro-15.0-AC, P3-Pro-20.0-AC,
P3-Pro-22.0-AC, P3-Pro-24.9-AC, P3-Pro-25.0-AC, P3-Pro-29.9-AC,
P3-Pro-30.0-AC

Ratings: See Annex

Manufactured by: FOXESS CO., LTD.
No.939, Jinhai Third Road, New Airport Industry Area, Longwan District, Wenzhou,
Zhejiang, China

Requirements: EN 50549-1:2019

This Test Certificate is granted on account of an examination by DEKRA, the results of which are laid down in a confidential file no. 6203338.50.

The examination has been carried out on one single specimen of the product. The Attestation does not include an assessment of the manufacturer's production. Conformity of his production with the specimen tested by DEKRA is not the responsibility of DEKRA.

This Test Certificate expires at the latest on 20 September 2029 or expires upon withdrawal of one of the above mentioned standards.

Shanghai, 20 September 2024

Number: 6203338.01COC

DEKRA Testing and Certification (Shanghai) Ltd.

Cliff Lin
Certification Manager

© Integral publication of this certificate and adjoining reports is allowed



DEKRA Testing and Certification (Shanghai) Ltd.

No.250, Jiangchangsan Road, Jing'an District, Shanghai, 200436 People's Republic of China

T +86 21 6056 7600 F +86 21 6056 7555 www.dekra-product-safety.com

ESA-CER-F021 v4.1

Document no. : 6203338.01COC

Ratings of the test product:

Model	H3-Pro-10.0 P3-Pro-10.0	H3-Pro-12.0 P3-Pro-12.0	H3-Pro-15.0 P3-Pro-15.0	H3-Pro-20.0 P3-Pro-20.0	H3-Pro-22.0 P3-Pro-22.0	H3-Pro-24.9 P3-Pro-24.9	H3-Pro-25.0 P3-Pro-25.0	H3-Pro-29.9 P3-Pro-29.9	H3-Pro-30.0 P3-Pro-30.0
Max PV input voltage (Vdc)	1000								
MPPT Voltage range (Vdc)	150-850								
Max input current (A)	16	16	32	32	32	32	32	32	32
Battery voltage (Vdc)	150-800								
Max. charge / discharge current (A)	50	50	50+50	50+50	50+50	50+50	50+50	50+50	50+50
Number of battery input	1	1	2	2	2	2	2	2	2
Norminal AC power (W)	10000	12000	15000	20000	22000	24900	25000	29900	30000
Max. apparent AC power (VA)	11000	13200	16500	22000	24200	24900	27500	29900	33000
Rated Output Voltage (Vac)	400 / 230 Vac, 380 / 220 Vac, 3L/N/PE								
Rated AC Frequency (Hz)	50/60								
Max. Output Current (A)	16.7	20.0	25.0	33.3	36.7	37.7	41.7	45.4	50.0
AC Output Power Factor	1(0.8 leading ...0.8 lagging)								
Max. AC Input Power (W)	15000	18000	22500	30000	33000	35000	35000	35000	35000
Rated grid voltage (Vac)	400 / 230 Vac, 380 / 220 Vac, 3L/N/PE								
Max. AC input current (A)	22.7	27.3	34.1	45.5	50.0	53.0	53.0	53.0	53.0
AC Input Power Factor	1(0.8 leading ...0.8 lagging)								
General Data	Operating temperature range: - 25 °C to + 60 °C, Protective class: I, Ingress protection rating: IP65, Altitude: 4000m.								

Model	AC3-Pro-10.0 P3-Pro-10.0-AC	AC3-Pro-12.0 P3-Pro-12.0-AC	AC3-Pro-15.0 P3-Pro-15.0-AC	AC3-Pro-20.0 P3-Pro-20.0-AC	AC3-Pro-22.0 P3-Pro-22.0-AC	AC3-Pro-24.9 P3-Pro-24.9-AC	AC3-Pro-25.0 P3-Pro-25.0-AC	AC3-Pro-29.9 P3-Pro-29.9-AC	AC3-Pro-30.0 P3-Pro-30.0-AC
Battery voltage (Vdc)	150-800								
Max. charge / discharge current (A)	50	50	50+50	50+50	50+50	50+50	50+50	50+50	50+50
Number of battery input	1	1	2	2	2	2	2	2	2
Norminal AC power (W)	10000	12000	15000	20000	22000	24900	25000	29900	30000
Max. apparent AC power (VA)	11000	13200	16500	22000	24200	24900	27500	29900	33000
Rated Output Voltage (Vac)	400 / 230 Vac, 380 / 220 Vac, 3L/N/PE								
Rated AC Frequency (Hz)	50/60								
Max. Output Current (A)	16.7	20.0	25.0	33.3	36.7	37.7	41.7	45.4	50.0
AC Output Power Factor	1(0.8 leading ...0.8 lagging)								
Max. AC Input Power (W)	15000	18000	22500	30000	33000	35000	35000	35000	35000
Rated grid voltage (Vac)	400 / 230 Vac, 380 / 220 Vac, 3L/N/PE								
Max. AC input current (A)	22.7	27.3	34.1	45.5	50.0	53.0	53.0	53.0	53.0
AC Input Power Factor	1(0.8 leading ...0.8 lagging)								
General Data	Operating temperature range: - 25 °C to + 60 °C, Protective class: I, Ingress protection rating: IP65, Altitude: 4000m.								

-End-